SPECIFICATION

Docket No. **0544MH-34056**

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN that WE, **Harri Rajala**, **Sami Lahti**, **Tapani Rautavirta**, **Samu Lahti**, and **Markus Salmi**, have invented new and useful improvements in a

METHOD AND APPARATUS FOR SUPPORTING MULTIPLE ALTERNATIVE

GRAPHICAL USER INTERFACES IN COMPUTER-MODERATED ELECTRONIC

COMMERCE

of which the following is a specification:

BACKGROUND OF THE INVENTION

1.   Field of the Invention:

The present invention relates in general to computer-moderated methods of conducting commercial transactions, and in particular to graphical user interfaces utilized for electronic commerce.

2.   Description of the Prior Art:

There has been a sudden increase in the utilization of electronic commerce for the sale of goods and services. This is especially true with the explosion of activity related to Internet commerce, but is also true for commerce conducted utilizing distributed data processing systems which require a dial-in or other similar connection. A great amount of detailed information can be provided to potential buyers over the Internet or a distributed data processing system. This gives the buyer a greater number of choices. And it also gives the seller a greater number of opportunities and options for merchandising its goods or services.

Modern electronic commerce depends on a number of interchanges between potential buyers and sellers through a series of dialog boxes in cascading graphical user interfaces. Such graphical user interfaces include a variety of relatively conventional graphical components which are utilized to communicate the options which are available to the buyer, and to receive the buyer's selection. Typically, the options available to the potential customer are set forth in a manner which allows buttons to be depressed through manipulation of the graphical pointing device. In other words, most of the transaction "dialog" is conducted through the presentation of a series of options to the potential

2

1 customer and a recordation of the customer's selection of the particular options through

2 the use of a graphical pointing device.

3

4 A variety of relatively well-known companies have relied heavily upon Internet-moderated

5 commercial transactions. One leader in this area is Dell Computer Corporation of Round

6 Rock, Texas. Dell has positioned itself well within the computer hardware market by

7 relying extensively upon the Internet to conduct a relatively extensive dialog with potential

8 customers, all moderated through a series of graphical user interface screens, which

9 present the customer with a variety of options and choices. Through such reliance on the

10 Internet, Dell has been able to keep its overhead low, turn its inventory often, and obtain

11 good results for its shareholders in terms of marketshare growth, increased dividends, and

12 rapid increases in stock value. Dell is just one example of the increasing and highly

13 effective use of the Internet to conduct commerce.

14

15 For those engaged in electronic commerce, any means which can be utilized to further

16 reduce costs and to stabilize operations will likely be appreciated and adopted.

17

SUMMARY OF THE INVENTION

It is one objective of the present invention to provide an improved method and apparatus for supporting multiple alternative graphical user interfaces in computer-moderated electronic commerce.

It is another objective of the present invention to provide an improved method and apparatus for supporting a low bandwidth graphical user interface for use in computer-moderated electronic commerce.

It is a particular objective of the present invention to provide an improved method and apparatus for supporting a low bandwidth HTML graphical user interface for use in computer-moderated electronic commerce.

These and other objectives are achieved as is now described.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the present invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of the preferred embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a simplified and pictorial representation of a distributed data processing system;

Figure 2 is a simplified block diagram representation of an inside sales business object server;

Figure 3 is a block diagram and pictorial representation of the scalability of the present invention which represents one commercially advantageous product feature;

Figure 4 is a block diagram and pictorial representation of the multithread capability of the computer moderated electronic commerce system of the present invention which represents another commercially advantageous feature;

Figure 5 is a block diagram and pictorial representation of an overview of the user interface options available utilizing the present invention which represents still another commercially advantageous product feature;

Figure 6 is a pictorial representation of an exemplary rule maintenance module;

1

2   Figure 7 is a pictorial representation of an exemplary dialog control screen in accordance

3   with the present invention;

4

5   Figure 8 is a pictorial representation of an exemplary dialog manager screen in

6   accordance with the present invention;

7

8   Figure 9 is a pictorial representation of an exemplary user interface maintenance

9   operation in accordance with the present invention;

10

11   Figure 10 is an exemplary pictorial and block diagram representation of a plurality of user

12   interfaces which may be supported utilizing the present invention;

13

14   Figure 11 is a flowchart representation of the utilization of a rendering engine to

15   dynamically construct a series of graphical user interfaces, in real time, and utilizing a

16   single database;

17

18   Figure 12 is a block diagram representation of the utilization of the present invention to

19   support multiple alternative rendering engines from a single database which maintains

20   metadata relating to the objects of the commercial transaction;

21

22   Figure 13 is a table of values used in conjunction with the preferred embodiment;

23

24   Figure 14 is an example illustrating element layout in an HTML environment;

25

1   **Figure 15** depicts a populated HTML page in accordance with a preferred embodiment of

2   the present invention; and

3

4   **Figure 16** is a flowchart illustrating an implementation of the preferred embodiment.

5

DETAILED DESCRIPTION OF THE INVENTION

1

2 With reference now to the figures and in particular with reference to **Figure 1**, there is

3 depicted a pictorial representation of the Internet 106 and a distributed data processing

4 system 108 either or both of which may be utilized to implement the method and system of

5 the present invention. As may be seen, distributed data processing system 108 may

6 include a plurality of networks, such as Local Area Networks (LAN) 110 and 132, each of

7 which preferably includes a plurality of individual computers 112 and 130, respectively. Of

8 course, those skilled in the art will appreciate that a plurality of Intelligent Work Stations

9 (IWS) coupled to a host processor may be utilized for each such network.

10

11 As is common is such data processing systems, each individual computer may be coupled

12 to a storage device 114 and/or a printer/output device 116. One or more such storage

13 devices 114 may be utilized, to store the various data objects or documents which may be

14 periodically accessed and processed by a user within distributed data processing system

15 108.

16

17 Still referring to **Figure 1**, it may be seen that distributed data processing system 108 may

18 also include multiple mainframe computers, such as mainframe computer 118, which may

19 be preferably coupled to Local Area Network (LAN) 110 by means of communications link

20 122. Mainframe computer 118 may also be coupled to a storage device 120 which may

21 serve as remote storage for Local Area Network (LAN) 110. A second Local Area Network

22 (LAN) 132 may be coupled to Local Area Network (LAN) 110 via communications

23 controller 126 and communications link 134 to a gateway server 128. Gateway server 128

24 is preferably an individual computer or Intelligent Work Station (IWS) which serves to link

25 Local Area Network (LAN) 132 to Local Area Network (LAN) 110.

26

1   As discussed above with respect to Local Area Network (LAN) 132 and Local Area

2   Network (LAN) 110, a plurality of data processing procedures or documents may be stored

3   within storage device 120 and controlled by mainframe computer 118, as Resource

4   Manager or Library Service for the data processing procedures and documents thus

5   stored.

6

7   Of course, those skilled in the art will appreciate that mainframe computer 118 may be

8   located a great geographical distance from Local Area Network (LAN) 110 and similarly

9   Local Area Network (LAN) 110 may be located a substantial distance from Local Area

10   Network (LAN) 132. That is, for example, Local Area Network (LAN) 132 may be located

11   in California while Local Area Network (LAN) 110 may be located within Texas and

12   mainframe computer 118 may be located in New York.

13

14   **Figure 1** also shows a graphical representation of a connection between local area

15   network 110 and the Internet 106 (World Wide Web) which is a wide area network

16   connecting thousands of disparate networks in industry, education, government, and

17   research, which utilizes TCP/IP as the standard for transmitting information. As is shown

18   in the view of **Figure 1**, a plurality of buyers (B1, B2, B3) may connect through the Internet

19   106 to local area network 110 which, for purposes of explanation, represents a local area

20   network under the control of a seller conducting electronic commerce. Alternatively, and

21   simultaneously, a plurality of buyers (B4, B5, B6) may make a dial-in connection through

22   gateway server 128 to local area network 110 in order to conduct electronic commerce

23   with the seller which maintains control over local area network 110. The seller may utilize

24   either or both the Internet connection or dial-in connection in order to communicate

25   simultaneously with a number of buyers, including B1, B2, B3, B4, B5, and/or B6.

26

1   **Figure 2** is a simplified block diagram representation of an inside sales business object

2   server 202 which is connected via read/write bus 206 to sales data server 204. Sales

3   business object server 202 is composed of a number of software packages which are

4   dedicated to particular electronic commerce functions. A read/write bus 206 allows sales

5   business object server 202 to read data from sales data server 204, and also allows sales

6   business object server 202 to write data to the sales data server 204. The sales business

7   object server 202 includes a suite of server services modules 208 and a suite of data

8   model modules 210. Preferably, the server services modules 208 include a session

9   management module 212, a product data module 214, a document generator module 216,

10   a pricing engine module 218, a configuration engine module 220, and a quote/shopping

11   cart module 222. The session management module 212 is utilized to control the electronic

12   dialog between each buyer or potential buyer and the seller and typically includes product

13   names, product serial numbers, product descriptions, and product fact sheets as well as

14   other similar information. The product data module 214 includes product information about

15   the product array offered by the seller. The document generator module 216 is utilized to

16   generate printed materials which support the electronic transaction, such as shipping and

17   invoice documentation. The pricing engine module 218 is utilized to allow the seller to

18   intelligently and accurately generate the total or "end" price to the customer. Preferably,

19   the pricing engine module will take into account differences in currency, various discounts

20   offered by the seller, the cost of freight and shipping, and the cost of warranties and

21   extended service options. The configuration engine module 220 is utilized in order to at

22   least partially automate a process through which the customer's needs are analyzed.

23   Additionally, the configuration engine module is utilized to determine component

24   compatibility in order to prevent the attempted combination of parts, components, or

25   assemblies which are incompatible or not optimal. The quote/shopping cart module 222 is

26   utilized to generate quotation documentation (both electronic and paper documents), if

10

1   necessary, and which builds automatically a quotation based upon configuration

2   information, price information, and quote information.

3

4   The data model modules 210 includes a plurality of software modules including a quote

5   identification module 224, a quote version module 226, a configuration module 228, and a

6   customer module 230. The quote identification module 224 is utilized to keep track of the

7   identification of various quotes made to potential and actual customers. The quote version

8   module 226 allows the system to keep track of a series of quotations to potential

9   customers and actual customers in order to prevent inconsistencies between quotes, or

10   other losses of information. The configuration module 228 maintains any information

11   relating to particular potential or proposed configurations. The customer module 230

12   maintains customer information such as identity, address, telephone, payment method,

13   and similar information.

14

15   Collectively, the server services modules 208 and data model modules 210 cooperate to

16   allow orderly and efficient communication between the seller and potential buyers through

17   sales data server 204.

18

19   Some advantages that may be obtained utilizing the present invention are graphically

20   depicted in **Figures 3** and **4**. **Figure 3** is a block diagram and pictorial representation of

21   the scalability of the present invention which represents one commercially advantageous

22   product feature, while **Figure 4** is a block diagram and pictorial representation of the

23   multithread capability of the computer moderated electronic commerce system of the

24   present invention which represents another commercially advantageous feature. As

25   depicted in **Figure 3**, a database server 240 may support a plurality of sales data servers,

26   including sales data servers 204, 242. Each of the sales data servers 204, 242 may in

1   turn support a number of sales business object servers. For example, sales data server

2   204 may support sales business object servers 244, 246, 248; additionally, sales data

3   server 242 may support sales business object servers 250, 252, 254. In this manner, the

4   computer moderated electronic commerce system of the present invention can be scaled

5   in a pyramidal fashion which allows for a theoretically unlimited number of concurrent

6   users being supported.

7

8   The computer moderated electronic commerce system of the present invention also allows

9   simultaneous multithread operation, as is depicted in block diagram in pictorial form in

10   **Figure 4.** As is shown, a data server 260 may be utilized to allow database connection

11   pooling. This optimizes the efficiency of database resource utilization. In the preferred

12   embodiment, an oracle database may be utilized. The data server 260 provides the data

13   to the application server layer which is composed of a number of separate components,

14   some of which were discussed above in connection with **Figure 2**. As is shown, sales

15   data server 204 is communicatively and operationally coupled with sales business object

16   server 202 which is capable of supporting a number of simultaneous electronic commerce

17   communication sessions including sessions 270, 272, 274, 276. The sales business

18   object server 202 is communicatively and operationally coupled to sales internet server

19   280 which is in turn communicatively and operationally coupled to web server 282. Web

20   server 282 allows for the simultaneous communication with potential buyers at and utilizing

21   computing devices 290, 292, 294, 296, and 298. Essentially, sales business object server

22   202 is a multithread server which utilizes multiprocessor servers. Multiple user sessions

23   may be enabled in one process, which makes for efficient use of the operating system

24   resources. The utilization of web server 282 and Internet sales server 280 facilitates

25   relatively low-cost simultaneous communication with buyers and potential buyers. The

26   communication between web server 282 and the computers (290, 292, 294, 296, and 298)

12

1 which are under control of the buyers and potential buyers is conducted utilizing a

2 relatively low bandwidth HTML dialog.

3

4 In the prior art, companies that conducted electronic commerce did so utilizing a Windows-

5 based graphical user interface which was accessed through conventional dial-in

6 operations. The Windows-based graphical user interface typically communicated with a

7 tabular database (such as a Sequel database). The bandwidth for communication

8 between the Windows-based graphical user interface and the tabular database was

9 relatively large in comparison with the bandwidth available for HTML-moderated

10 communications via the Internet. As a practical manner, many entities that currently

11 conduct electronic commerce have significant investment in non-Internet facilities including

12 dial-up capabilities and Windows-based graphical user interfaces, as well as substantial

13 investments in databases relating to the products, pricing, and customers. As electronic

14 commerce migrates from dial-up sessions (where bandwidth presented no real problems)

15 toward Internet-based communications (where bandwidth becomes a substantial problem)

16 a significant number of problems must be resolved. Preferably, and in accordance with

17 the present invention, an entity's investment in its electronic commerce systems need not

18 be wasted. In accordance with the present invention, a variety of graphical user interfaces

19 may be constructed and maintained, without requiring reinvestment in, or recreation of, the

20 databases which supported such electronic commerce.

21

22 **Figure 5** is a block diagram and pictorial representation of an overview of the interface

23 options available utilizing the present invention which represents still another commercially

24 advantageous product feature. The view of **Figure 5** represents the different layers of

25 processing which must be implemented in order to provide the system of the present

26 invention. As is shown, the data server 260 maintains the metadata which is utilized

13

1   during the commercial transaction. This may include component identification and

2   component property of the various items offered for sale by the seller. The data server

-3   260 communicates with the sales data server 204. The sales data server 204

4   communications with the sales business object server 202. The sales business object

5   server 202 may communicate over communication link 303 with data processing system

6   296. The communication between the sales business object server 202 and data

7   processing system 296 may be conducted utilizing the JAVA programming language;

8   therefore, the client-user interface is supported by JAVA and communication is conducted

9   over a local area network or a high speed wide area network.

10

11   An alternative means of communicating with buyers is also provided. As is shown in

12   **Figure 5**, sales internet server 280 may also communicate with sales business object

13   server 202. Web server 282 in turn communicates with sales internet server 280. Web

14   server 282 communications intermittently over communication link 300 utilizing an HTTP

15   protocol. Communication is conducted with one or more data processing systems such as

16   data processing system 290. Data processing system 290 is operating in a Web browser

17   mode of operation. Communication between data processing system 290 and Web server

18   282 is conducted utilizing HTML. The communication link 300 is a low-speed wide-area

19   network or internet connection. The view of

20

21   **Figure 5** shows two different user interfaces which are supported by the data maintained

22   in data server 260. The dialog which makes up the content of the electronic transaction is

23   constructed dynamically by the sales data server 204 and sales business object server

24   202 utilizing the metadata maintained on data server 260. In this way, a single data base

25   may be utilized to support a plurality of simultaneous transaction dialogs in a plurality of

14

1 differing programming interfaces supported by different programming languages and over

2 communication links with different capabilities.

3 **Figure 6** is a pictorial representation of an exemplary rule maintenance module.

4 The content of the dialog may be maintained utilizing such a rule maintenance system

5 which allows for the visual mapping of information. In this manner, the various

6 components, sub-assemblies, and buyer options may be mapped out in a logical manner.

7 The dialog between the seller and potential buyers may be constructed utilizing a "Dialog

8 Control" module, which is depicted in **Figure 7**, and maybe manually generated utilizing a

9 "Dialog Manager" module which is depicted in **Figure 8**. As is shown, the Dialog Control

10 module in **Figure 7** is utilized to enumerate the various dialog controls which are

11 associated with a particular graphical interface screen. The example depicted in **Figure 7**

12 relates to a dialog I.D. relating to the "chassis" of a vehicle. The seller may utilize the

13 various command buttons on the right side of the screen to, add, delete, edit, clear the

14 various controls which can be, or are, in fact, associated with a particular graphic user

15 interface. The Dialog Manager in **Figure 8** depicts the dialog associated with a "cabin"

16 graphical user interface. As is shown, the dialog includes ListBox1, ListBox3, CheckBox1,

17 ListBox4, ListBox2, TextBox1, CheckBox2, and PushButton1. Each one of these

18 graphical user interface items has various "property" and "value" attributes associated

19 therewith. **Figure 9** depicts a number of simultaneously open and overlapping screens,

20 including a Sales Maintenance screen which maps the relationship between the

21 components, a Dialog Manager screen which lists the various dialog items associated with

22 the "cabin" graphical user interface, and a Dialog Editor screen which is utilized to edit the

23 Dialog Manager screen. Utilizing these functions, all of which are known in the prior art,

24 one may construct graphical user interface screens which are logically linked to one

25 another, which include a variety of dialog items, and which may be edited when product

26 content changes.

15

Figure 10 is a pictorial and graphic representation of the maintenance of the various user

interfaces in accordance with the preferred embodiment of the present invention. As is

shown, a product rule set 310 is utilized to map or organize the various product features

and options which are offered by the seller to potential buyers. The Dialog Controls

module 312 is utilized to control the content of the dialog boxes of a graphical user

interface. The content may be edited utilizing Dialog Editor 314. In accordance with the

preferred embodiment of the present invention database 260 maintains the metadata

associated with the product line and options which are set forth in the product rule set 310.

Database 260 supports a variety of rendering engines which are utilized to generate

graphical user interface screens as part of the dialog transaction. As is shown, JAVA-

rendering engine 320 accesses database 260 in order to generate dynamically and in real

time user interface 326 which is a JAVA applet. HTML-rendering engine 322 utilizes

database 260 to generate dynamically and in real time graphical user interface screen 328

which is an HTML user interface. C++-rendering engine 324 utilizes data from database

260 to generate dynamically and in real time graphical user interface 330. Note that

graphical user interfaces 326, 328, and 330 are all very similar in their content and layout,

even though they are generated in different operating environments utilizing different

programming languages. All of the rendering engines 220, 222, and 224, make dynamic

use of the Dialog Control box 312 in order to generate the graphical user interfaces 326,

328, and 333.

A method and apparatus is provided which allows for a single database to support

dynamically a number of multiple alternative graphical user interfaces, all in order to allow

computer moderated electronic commerce. The database interacts with a number of

rendering engines which utilize metadata maintained in the database to dynamically

16

1 generate an electronic commerce transaction dialog in a plurality of different

2 communication, operation, and programming environments. For example, the present

3 invention may be utilized to simultaneously support graphical user interfaces constructed

4 utilizing the programming language C++. Alternatively, and additionally, the system may

5 support a graphical user interface constructed utilizing the JAVA programming language.

6 Alternatively, and additionally, the invention allows a single database to support a relatively

7 low band with communication in an internet environment utilizing the HTML programming

8 language. In accordance with the present invention, the differing graphical user interfaces

9 may have the same general appearance and the same series of dialog boxes in order to

10 enable the electronic commerce.

11

12 **Figure 11** is a flowchart representation of the utilization of a rendering engine to

13 dynamically construct a series of graphical user interfaces, in real time, and utilizing a

14 single database. The process starts at block 402, and continues at block 404, wherein

15 communication is established between a buyer and a seller. This communication will

16 occur over a particular communication channel. For example, the buyer may make contact

17 with the seller utilizing the Internet by accessing the seller's website. Alternatively, the

18 buyer may dial-in to a wide area network utilizing conventional telecommunications

19 modem connections in order to communicate with the seller utilizing a graphical user

20 interface constructed in the conventional manner utilizing the C++ programming language.

21 Alternatively, the potential buyer may make communication with the seller utilizing JAVA

22 applets. All three of these scenarios are alternatives to one another and are graphically

23 depicted in **Figure 10**. In accordance with step 406, the seller's data processing system

24 activates the appropriate rendering engine which is suited for the mode and channel of

25 communication which has been established by the buyer. For example, the buyer is

26 making contact utilizing the Internet, the HTML rendering engine will be activated. Then,

17

1   in accordance with step 408, the seller's data processing system calls the appropriate

2   dialog manager module. In actual practice, an electronic transaction is composed of a

3   series of cascading and logically-linked graphical user interfaces. Each graphical user

4   interface has associated with it a particular dialog manager module, as is conventional.

5   The dialog manager module identifies each and every component of the graphical user

6   interface which will be presented to the buyer. Some of the components are "inactive"

7   components and merely present images, data, or information; however, other elements of

8   the graphical user interface are "active" elements which are adapted to receive user input

9   typically through the detection of the operator actuation of the graphical pointing device

10   (typically the depression of the left button on the mouse associated with the buyer's

11   computer). Then, in accordance with step 410, the seller's data processing system utilizes

12   the rendering engine to generate an associated graphical user interface. Concurrently

13   with this step, and as is set forth in step 412, the data processing system of the seller

14   communicates with a single database in order to read metadata which is associated with

15   the graphical user interface. As described above, the metadata may be arranged utilizing

16   conventional tools such as a rule maintenance module. The metadata may comprise

17   simple product number and feature information; however, in alternative electronic

18   transactions, the metadata may comprise a substantial body of transaction and product

19   information. The more complex the subject matter of the electronic transactions, the more

20   likely there is to be associated with each graphical user interface a greater amount of

21   detailed information. This communication between the rendering engine and the single

22   database is conducted in real time and is done so dynamically during the interaction

23   between the seller's data processing system and the buyer's data processing system.

24   One significant advantage of this approach is that the seller need not maintain multiple

25   parallel databases for each rendering engine; instead, a single database may be

26   maintained. This is a low cost option since there are greater costs associated with

18

1   maintaining several parallel databases and it is often difficult to maintain consistency

2   between such databases.

3

4   In accordance with step 414, the data processing system under the control of the seller

5   applies the metadata dynamically and in real time during creation of the graphical user

6   interface. Then, in accordance with block 416, the seller's data processing system

7   monitors for the dialog in order to determine input or selection of options by the buyer. In

8   accordance with step 418, if necessary, the data processing system under the control of

9   the seller is utilized to write data to the database. Then, in accordance with block 420, the

10   data processing system which is under the control of the seller monitors for a termination

11   of the communication session. If the session is ended, the process ends at block 422.

12   However, if the session is not ended, the data processing system under control of the

13   seller monitors the dialog as conducted through the dialog boxes and returns to block 408,

14   wherein the appropriate dialog monitor module is called based upon the buyer's input. The

15   process repeats over and over again until the dialog is terminated. As a consequence of

16   the dialog, a substantial amount of detailed metadata is sequentially presented to the

17   potential buyer in a series of cascading graphical user interface dialog boxes. In turn, the

18   data and selections provided by the buyer may be recorded to the single database in order

19   to enable completion of the transaction or return to the transaction at a later date. It is

20   widely known that many electronic interactions do not result in a transaction at the first

21   contact. It may take several interactions with the buyer before a transaction is completed.

22   This is the reason that most electronic transaction systems have shopping carts which

23   may be preserved in memory and recalled at a later date by the buyer in order to allow the

24   buyer to modify or add to the shopping cart.

25

19

1   **Figure 12** is a block diagram representation of the utilization of the present invention to

2   support multiple alternative rendering engines from a single database which maintains

3   metadata relating to the objects of the commercial transaction. As is shown in **Figure 12**,

4   the buyer system 500 communicates with a data processing system under control of the

5   seller through communication channel 504. The communication channel may be a dial-in

6   modem connection or an Internet connection. The mode of accessing the seller's data

7   processing system will determine which particular one of a number of available alternative

8   rendering engines are employed by the seller's data processing system. As is shown in

9   **Figure 12**, rendering engines 506, 508, 510 may be utilized to support a variety of

10   alternative communication modes. For example, if the various rendering engines may

11   support communication through JAVA scripts, HTML protocols, or through a graphical user

12   interface constructed utilizing C++. Alternatively, other different programming languages

13   and communication modes may be supported by different rendering engines. Once the

14   appropriate rendering engine is selected, it communicates with a dialog manager module

15   512. The dialog manager module communicates through rule maintenance module 518 to

16   database 520 which contains product metadata. The dialog manager modules correspond

17   to various graphical user interfaces which are provide to the buyer's system 500 during a

18   series of dialog box communications. The dialog manager module 512 is constructed

19   utilizing a dialog editor 516 through available dialog controls 514. The rendering engine

20   506 may pass information to database 512 for recordation.

21

22   Alternatively and/or concurrently, a number of buyers including buyers 502 and 522 may

23   communicate through communication channels 524, 526 with alternative rendering

24   engines including rendering engines 508, 510. These electronic transactions are

25   communicated through a series of graphical user interfaces which present a series of

26   dialog boxes to the buyer's system 502, 522 and which receive the input of the buyer and

20

1 selections of the buyer through monitoring the utilization of the graphical pointing device.

2 Rendering engines 508, 510 also access database 520 through dialog manager 512 and

3 rule maintenance module 518. In this manner, a single database 520 is utilized to support

4 a plurality of alternative rendering engines 506, 508, 510, which allow for simultaneous

5 concurrent communication over different communication channels 504, 524, 526 with a

6 plurality of buyer data processing systems 500, 502, 522.

7

8 The dialog editor 516 of **Figure 12** is similar to a dialog editor utilized for creating and

9 editing dialogs for the "rhythm" product of i2 Technologies, assignee of the present

10 application. It includes many editing functions which allow a dialog to be either created or

11 edited. Such functions include the following specific functions:

- 12   • NEW: This command allows the programmer to create a new dialog box.

- 13   • OPEN: This command allows the programmer to open an existing dialog

- 14   box template.

- 15   • SAVE: This command allows a programmer to create a file for the current

- 16   dialog box template and save that template to the file.

- 17   • SAVE AS: This command allows the programmer to save the current dialog

- 18   box template in a file under a new name.

- 19   • TEST DIALOG: This command allows the programmer to toggle between a

- 20   run mode in which the dialog box "comes alive" for testing purposes in an

- 21   edit mode in which one can make changes to the dialog box.

- 22   • CAPTURE DIALOG: This command allows the programmer to capture

- 23   standard window controls from a standard window dialog box in another

- 24   windows application.

- 25   • EXIT: This command allows a programmer to close the dialog editor

- 26   module.

21

1   • <u>EXIT AND RETURN</u>: This command allows a programmer to close a dialog

2   editor and return to the host application.

3   • <u>EDIT MENU</u>: This command allows a programmer to undue up to ten

4   preceding operations.

5   • <u>CUT</u>: This command allows the programmer to select a dialog box control

6   from an application window and place it on a clipboard.

7   • <u>COPY</u>: This command allows the programmer to copy a selected dialog box

8   control without removing it from the dialog editor's application window and

9   places it on a clipboard.

10   • <u>PASTE</u>: This command allows the programmer to insert the contents of the

11   clipboard into a dialog editor.

12   • <u>CLEAR</u>: This command removes a selected dialog box control from the

13   programmer's application window without placing it on the clipboard.

14   • <u>DUPLICATE</u>: This command allows a programmer to create a duplicate

15   copy of a selected control.

16   • <u>SIZE TO TEXT</u>: This command allows a programmer to adjust the board as

17   to certain controls to fit the text displayed on them.

18   • <u>GRID</u>: This command allows a programmer to display a grid dialog box

19   which can be used to display or turn off the grid and adjust the grid spacing.

20 The Dialog Editor 516 further includes a number of commands which are utilized to add

21 control or communication elements to a particular user interface. Some principal control

22 menu items include the following:

23   • <u>OK BUTTON</u>: This command adds a default "OK" button to a dialog box.

24   • <u>CANCEL BUTTON</u>: This command allows the programmer to add a default

25   cancel button to a dialog box.

- <u>HELP BUTTON</u>: This command allows the programmer to add a help button to a dialog box.

- <u>PUSH BUTTON</u>: This command allows the programmer to add a push or command button to a dialog box.

- <u>OPTION BUTTON</u>: This command allows the programmer to add an option button to a dialog box. An option button is one of two or more link buttons that let user select only one from a group of mutually exclusive choices.

- <u>CHECK BOX</u>: This command allows the programmer to add a check box to a dialog box. Users can check or clear a check box to indicate their preference regarding the alternatives specified on the check box label.

- <u>GROUP BOX</u>: This adds a group box to a dialog box. A group box is a rectangular design element used to enclose a group of related controls. One can use the optional group box label to display a title for the controls in the box.

- <u>TEXT</u>: This command allows a programmer to add a text control to a dialog box. A text control is a field containing text you want to display for the user's information. The text in this field wraps, and the field can contain a maximum of 255 characters. Text controls can either display stand-alone text or be used as labels for text boxes, list boxes, combo boxes, drop list boxes, pictures, and picture buttons. One can choose the font in which the text appears.

- <u>TEXT BOX</u>: This control allows the addition of a text box to a dialog box. A text box is a field in which users can enter text (potentially, as much as 32K). By default, this field holds a single line of non-wrapping text. If one chooses a multi-line setting in the text box,, this field will hold multiple lines of wrapping text.

23

1   • LIST BOX: This adds a list box to a dialog box. A list box is a displayed,

2   scrollable list from which the user can select one item.

3   • COMBO BOX: This adds a combo box to a dialog box. A combo box

4   consists of a text field with a displayed, scrollable list beneath it. Users can

5   either select an item from the list or enter the name of the desired item in the

6   field text. The currently selected item is displayed in the field text. If the item

7   was selected from the scrolling list, it is highlighted there as well.

8   • DROP LIST BOX: This adds a drop list box to a dialog box. A drop list box

9   consists of a field that displays the current selected item, followed by a

10   downward-pointing error which users can click to temporarily display a

11   scrolling list of items. Once they select an item from the list, the list

12   disappears and the newly selected item is displayed in the field.

13   • PICTURE: This command adds a picture to a dialog box. A picture is a field

14   used to display a windows bit map or metafile.

15   • PICTURE BUTTON: This adds a picture button to a dialog box. A picture

16   box is a special type of push, or command button on which a windows bit

17   map or metafile appears.

18   • PICT TOOL: This enables a programming to select, move, and resize, items

19   that control the insert point.

20   The dialog editor of 516 can be considered to contain a pallet of functions, commands,

21   and graphical elements which may be selected by a programmer in establishing the

22   contents of a dialog which consists of one or more cascading or linked graphical user

23   interfaces. The programmer utilizes the elements in the dialog editor in order to construct

24   and edit a dialog.

25

The dialog controls module 514 is comparable to a dialog controls module present in the "rhythm" product sold by i2 Technologies, Inc. Assignee of the present application. This module allows one to connect structure boxes to dialog controls one has created utilizing the dialog editor 516. An exemplary screen from the dialog controls module 514 of **Figure 12** is depicted in **Figure 7**. As is shown, a "NAME 601" field is provided which displays the name of the active structure box. Additionally, a "CODE FIELD 603" is provided which displays the code of a selected box. One can select another code from a drop down list. The boxes are listed in the same order as they appear in the structure. When a particular code is identified in Code Box 603, a grid 605 is displayed there below which displays all dialogs, controls and variables that have been earlier designated as being associated with the box or boxes. As shown in **Figure 3**, a grid 605 includes a variable field 607, a dialog ID field 609 and a control field 611.

The same screen depicted in **Figure 7** also depicts a series of fields which identify dialogs. A dialog name Box 613 is provided which identifies a particular dialog. A dialog ID box 615 displays a dialog ID that one has entered for a dialog in the dialog manager. A dialog control box 617 displays the dialog controls that have been created utilizing the dialog editor 516 of **Figure 12**.

As is shown in **Figure 7**, a variety of control buttons are provided including an "OK" button, a "cancel button", "scrolling" buttons, a "variables" button which opens a variables dialog, a "clear" button which clears the PM variable from the selected control for the active box. An "add" button which can be utilized to add controls. A "delete" button which removes selected control from the active box, an "update" button which updates the active dialog and control as new ones in the grid, an "edit" button which opens the dialog manager

25

1   dialog, a "show" button which displays the dialog with the box codes attached to the

2   controls, and a "close" button which closes the show dialog.

3

4   An exemplary screen from the dialog manager 512 of **Figure 12** is depicted in the view of

5   **Figure 8**.   This dialog manager is similar to the dialog manager present in the

6   "RHYTHMS" product of i2 Technologies which is the Assignee of the present application.

7   The exemplary dialog manager screen includes an ID field 651 which displays the ID of

8   the active dialog. A drop down list may be provided to allow the selection of another

9   dialog. It further includes a name field 653 which displays the name of the active dialog. It

10   contains a controls field which displays a list of controls related to the active dialog. The

11   controls are buttons, radio buttons, group boxes, etc.

12

13   A properties grid 657 is also provided which contains the values from the dialog editor

14   established for graphical user interface elements. A plurality of control buttons are also

15   provided in the view of **Figure 8**. A programmer may create a new dialog by clicking the

16   "ADD" button. The programmer may create a new dialog by clicking the "DLG EDITOR"

17   button. The scrolling buttons are provided to allow backwards and forwards scrolling. A

18   "SAVE" button is provided to allow the saving of a edited or newly created dialog. The

19   "DELETE" button allows the deletion of an active dialog.

20

21   **Figure 13** is a table which identifies the primary values which are under the parameters

22   control. A "CLASS" value cannot be edited. However, the X and Y coordinates may be

23   edited. These X and Y coordinates establish an X and Y coordinate in pixels for a

24   graphical user interface element. The Y variable displays the width of the control element

25   in pixels and the value H displays the height of the control element in pixels. The "TITLE"

26   element is a field for displaying the title of the control. The "OPTION" group cannot be

1   edited. The "TEXT" element identifies a default static control text. The "FONT" element

2   establishes a font name, size, and style. The "MULTI-LINE" element identifies an edit

3   control feature in which a multiple or single line text may be identified. The "RTF" and

4   "RTF TOOLBAR" elements identify a text box that can contain RTF text (Microsoft's rich

5   text format). The "EXTENDED" element identifies a multi-select list box that includes a

6   check box for items in that list box.

7

8   Determining the relative position of all of the elements in a graphical user interface is a

9   relatively simply matter when the operating environment and language is suitable for

10 relatively high-bandwidth communication. For example, graphical user interfaces encoded

11 in C++ or JAVA are relatively easy to implement using the present invention. However,

12 graphical user interfaces which utilize HTML are a little more complicated to implement

13 since there is no X,Y (coordinate system) in an HTML environment. In accordance with

14 one implementation of the present invention, the elements of a graphical user interface

15 may be located in HTML tables which can be utilized to emulate an X, Y coordinate

16 system and which can be utilized in real time to properly locate the user interface

17 elements. When operating an HTML environment, the present invention allows an HTML

18 page to resemble graphical interface layouts for alternative rendering engines such as

19 C++ and JAVA, utilizing a single database. Accordingly, the present invention allows a

20 single database to support multiple user interface environments so separate parallel

21 databases need not be maintained.

22

23 **Figure 14** is a pictorial representation of how elements in a graphical user interface in an

24 HTML environment are laid-out in accordance with the preferred embodiment of the

25 present invention. As is shown, HTML page 400 is divided up into segments which cover

26 the entire space that is available. In the HTML format, this is considered to be a irregular

27

1   table. The space within HTML page 700 will be accounted by a "cell" within the table even

2   if there is no text or image provided in that particular portion of Page 700. In the view of

3   **Figure 14**, "cells" which do not contain any text or images are shown in dashed outlined

4   form. Portions of the graphical interface which include text or images are shown in solid

5   line form. The space within HTML page 700 may be divided up into rows. The first row is

6   made up of cells 701, 703, 705, 707. Of these, cell 707 does not include any text or image

7   portions. It is merely space which is not utilized. The cell 707 is utilized by the program in

8   order to "account" for the space. The second row includes cells 709, 711, and the upper

9   portion of cell 713. Cell 711 does not contain any text or images and is utilized merely to

10   account for the space between cell 709 and cell 713. The third row is made up of cells

11   715, 717, 719, 721, and 713. Of these, cells 715, 721 are regions which do not contain

12   any text or images and which are utilized only to account for the space in that row. The

13) next row includes cells 723, 725, 727, 729, 731. Cells 725, 729 include text and/or images

14   while cells 723, 727, 731 do not include any text or images and are merely utilized to

15   account for the space in that row. This row also includes the portion of cell 713. The next

16   row is made of cells 733, 735, 737, 739, 741, 713. Of these cells, cells 733, 737, 741 are

17   not utilized for depicting any text or images and are merely utilized to account for the

18   space in that row. The next row includes cells 743, 745, 747, 749, 751 and 713. Cells

19   745, 749, 713 include text and/or images. Cells 743, 747, 751 do not include text or

20   images. The next row includes cells 753, 755, 757. Cells 755, 757 include text and/or

21   images while cell 753 does not include any text or images. The final row is made of cell

22   759.

23

24   **Figure 15** depicts HTML page 15 with cells populated with text and images in accordance

25   with the Dialog Controls 514 and Dialog Manager 512 of **Figure 12**. As is shown, cell 701,

26   703, 705 include textual material. Cell 713 includes a photo of the product. Cells 709,

1   717, 719 include textual material relating to product features. Cell 725, 735, 745, 729,

2   739, 749 include active areas which receive operator selections. Cell 755, 757 include

3   buttons. Cell 759 includes scroll back and log out text. Examination of **Figures 14** and **15**

4   reveals that the table layout of HTML page 700 is useful for managing the relative position

5   and size of the elements of the graphical user interface.

6

7   A routine which implements the preferred embodiment of the present invention is depicted

8   in the flow chart of **Figure 16**. The process starts at Block 801, and goes to Block 803,

9   wherein the product model is loaded. Next, in accordance with Block 805, the Dialog

10   Controls Module is loaded. Then, in accordance with Block 807, the Dialog Manager is

11   loaded. Next, in accordance with Block 809, the Dialog Controls Module is searched for

12   the particular product model. Once it is located, the values associated with that particular

13   product model are read from the Dialog Controls Module. Then, in accordance with Block

14   813, the size of the user interface elements are adjusted if necessary in order to have the

15   "cells" sized to an extent sufficient to carry all of the text and/or images which are to be

16   posted in that particular portion of the HTML page. This can be best understood with

17   reference again to **Figure 14**. For the third row from the top, the text resident in cells 717,

18   719 may require a greater or lesser amount of space. If these cells need to be expanded,

19   space that is not dedicated for some other purpose can be utilized. For example, cells

20   517, 521 may be further reduced in order to allow a greater amount of text or images to be

21   posted to that portion of the HTML page 700. Sizing issues may become more complex if

22   fonts sizes are changed for a particular graphical user interface. Changes in font size will

23   necessitate recalculation of the available cell space and enlargement of the cells dedicated

24   for text in order to accommodate the enlarged text.

25

1 Returning now to **Figure** 815, once the user interface elements are adjusted in size, then

2 the user interface is populated with its elements in accordance with Block 815 and the

3 process ends at Block 817.

4

5 One principal advantage of the present invention is that existing databases can be utilized

6 to populate on HTML pages which serve as graphical user interfaces. This can be done

7 without creating any new or separate parallel database for the same types of data. The

8 present invention can be applied to a wide variety of programming environments and

9 programming languages. The basic concept is to utilize a single data base and multiple

10 rendering engines in a controlled manner in order to enable the generation of generally

11 similar or comparable graphical user interface environments which utilize that single data

12 base to communicate with customers. In this manner, the customer may interact with a

13 seller in one programming environment/language on one occasion, but in another

14 programming environment/language on another occasion. In all locations, the graphical

15 user interface screens which are presented to the user will be generally comparable in

16 appearance. Furthermore, the data displayed on those pages will be identical since they

17 are drawn or pulled from a single database.

18

19 A feature of the present invention is that it can also be applied to multiple sellers, as well

20 as multiple buyers as described above. This would allow a flexible approach to commerce

21 for complex e-commerce systems.

22

23 Although the invention has been described with reference to a particular embodiment, this

24 description is not meant to be construed in a limiting sense. Various modifications of the

25 disclosed embodiments as well as alternative embodiments of the invention will become

26 apparent to persons skilled in the art upon reference to the description of the invention. It

1   is therefore contemplated that the appended clams will cover any such modifications or

2   embodiments that fall within the scope of the invention.

3